



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/674,682	09/29/2003	Yaron Elboim	42P16967	5118

8791 7590 03/28/2006

BLAKELY SOKOLOFF TAYLOR & ZAFMAN
12400 WILSHIRE BOULEVARD
SEVENTH FLOOR
LOS ANGELES, CA 90025-1030

EXAMINER

DILLER, JESSE DAVID

ART UNIT	PAPER NUMBER
----------	--------------

2187

DATE MAILED: 03/28/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 10/674,682	Applicant(s) ELBOIM ET AL.	
	Examiner Jesse Diller	Art Unit 2187	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 19 May 2005.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-22 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-13, 15, 16 and 20-22 is/are rejected.
- 7) ☒ Claim(s) 14 and 17-19 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

1. Claims 1-22 are pending in the application, and have been examined.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

2. Claim 15 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. Claim 15 recites that the identifying occurs after loading; however, this directly contradicts the parent claim 11, which states that the identifying occurs prior to loading. For examination purposes, the claim has been taken to read, "prior to loading."

Appropriate correction is required.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 1-2 and 5-7 are rejected under 35 U.S.C. 102(b) as being anticipated by Kao et al., US 6,119,192.

4. As for claim 1, Kao teaches:

- a non-volatile memory storing information to load a plurality of configuration registers of a device (160, Fig. 1), wherein
- the information includes a plurality of address information and a plurality of data corresponding to the plurality of address information (see address information 0, 5, 5m, 5n and data information 1-4, 6, 5m+1-5m+4, Fig. 5),
- each of the plurality of address information identifying at least one of the plurality of configuration registers to which a corresponding data should be written (see Fig. 5; the address information is an index referring to the appropriate register; see 365, Fig. 3).

5. As for claim 2, Kao additionally teaches:

- The non-volatile memory is an Electrically Erasable Programmable Read-only Memory (See Col. 3, line 43) and
- the configuration registers are used to define parameters for communication between the device and at least one other device (See Cols 1-2).

6. As for claim 5, Kao additionally teaches:

- the non-volatile memory has a memory size less than or equal to a memory size sufficient to fill all the configuration registers (The memory has a size equal to a memory size sufficient to fill some or all the configuration registers; see Col. 3, lines 10-15; Claim 2)

7. As for claim 6, Kao additionally teaches:

- a block of control logic coupled to the memory, the block of control logic to write the plurality of data to the plurality of configuration registers according to the plurality of address information (see 205, Fig. 2; for multiple logic blocks which control the loading).

8. As for claim 7, Kao additionally teaches:

- the plurality of configuration registers are to be loaded during an initialization of the device (Col. 3, lines 27-35: section b; the loading happens on startup).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

9. Claims 3-4, 8-10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kao in view of Bonaccia et al., US 2004/0143715.

10. As for claims 3-4, Kao teaches the limitations of claim 1, as above. Kao does not teach, however, that the device is an analog communication device, as does claim 3 or that the device is a processor, memory controller, or Ethernet controller, as does claim 4.

11. Bonaccio teaches a system and method for loading sets of configuration registers from a non-volatile memory. He teaches, in Pars. 4 and 20-21, that many ICs allow the user to configure the circuit using configuration registers. He cites several examples, such as in HD read channel controllers or microprocessors in Par. 4 and analog communications circuits in the last lines of Par. 6. Further, in Pars. 20-21, he teaches that the methods of loading configuration registers may be applied not only to ICs such as hard disk channel controllers, but to any IC configured by registers.

12. Kao and Bonaccio are analogous art, because they are from the same area of endeavor, namely systems for setting configuration registers.

13. At the time of the invention it would have been obvious to use the system of setting configuration registers as taught by Kao in an environment such as a microprocessor or analog communication circuit.

14. The motivation for doing so is taught by Bonaccio in Par. 4, namely that using programmable registers is widely used in many ICs to allow the user to configure the function of the chip. Further, Kao teaches in Col. 3, lines 60-66 that his invention would be beneficially used in many systems where it is desirable to configure a peripheral device in an expedited manner prior to a normal system initialization procedure.

15. Therefore, it would have been obvious to use the register loading process of Kao in different environments, thereby obtaining the invention of claims 3-4.

16. As for claim 8, Kao teaches:

- loading the plurality of configuration registers (365, Fig. 3; see also Col. 3, lines 27-35; section b) according to information stored in a non-volatile memory (160, Fig. 1), wherein
- the information in a memory includes a plurality of address information and a plurality of data corresponding to the plurality of address information, each of the plurality of address information identifying at least one of the plurality of to which a corresponding data should be written (see address information 0, 5, 5m, 5n and data information 1-4, 6, 5m+1-5m+4, Fig. 5; see also Fig. 5; the address information is an index referring to the appropriate register; see 365, Fig. 3).

Art Unit: 2187

17. Kao does not teach, however,

- resetting each of a plurality of configuration registers of a device to a register default data value before loading the registers.

18. **Bonaccio teaches** a system and method for loading sets of configuration registers from a non-volatile memory. He teaches, in Par. 6, that configuration values may come from several sources. Usually, the registers are made up of latches which are designed to be reliably reset to a specific state when power is first applied. He also teaches that rather than hard-wiring these values, a POR value memory, 14, Fig. 1, may be used to reset each of the configuration registers to a default value which can be changed and subsequently reset from the non-volatile memory.

19. Kao and Bonaccio are analogous art, because they are from the same area of endeavor, namely systems for setting configuration registers.

20. At the time of the invention it would have been obvious to modify the system of Kao to use the Power-on value memory taught by Bonaccio to reset the registers to a default value on power-up.

21. The motivation for doing so is taught by Bonaccio in Pars 6-7, namely that sometimes the default values are correct, and sometimes they need to be changed. Therefore, it would have been obvious to use the default register value of Bonaccio in the system of Kao, thereby obtaining the system of claim 8.

22. **As for claim 9, Kao also teaches:**

- The loading occurs during the initialization of a communication controller device (see 150-160, Fig. 1 and Fig. 2; the system is a PCI communications bus controller).

23. As for claim 10, Kao also teaches:

- updating the information stored in the non-volatile memory with a second plurality of address information and second a plurality of data corresponding to the second plurality of address information, each of the second plurality of address information identifying at least one of the plurality of to which a corresponding one of the second plurality of data should be written (Col. 7, lines 10-25).

24. Claim 11-13, 15-16 rejected under 35 U.S.C. 103(a) as being unpatentable over Bonaccio in view of Kao.

25. As for claims 11, 15, Bonaccio discloses:

- selecting a desired configuration of a device, the desired configuration associated with desired data to be stored in a plurality of registers of the device; (see Par. 9; also Par. 29, first 5 lines; also first half of Par. 27; the start register designates a configuration set)
- storing test information associated with the desired configuration in a memory (Par. 29, Fig. 1; the configuration sets are test information associated with various configurations);
- resetting each of the plurality of registers to a register default data value (Par. 6);
- loading at least two of the plurality of registers according to the test information (Par. 32),

- identifying a subset of the plurality of test data that correspond to a subset of the plurality of registers having default data values equal to desired data for achieving the desired configuration *prior* to loading (*NOTE: see section entitled Claim Rejections – 35 USC § 112. See Fig. 1, Par. 23; loading a single set may load less than all of the registers. In other words, a desired configuration may identify a few registers to be updated; for the rest, the default value is the correct one*).

26. Bonaccio does not expressly disclose that

- the test information includes a plurality of test address information and a plurality of test data corresponding to the plurality of test address information, each of the plurality of test address information identifying at least one of the plurality of registers to which a corresponding test data should be written

27. Instead, Bonaccio teaches that the configuration sets stored in the non-volatile memory contain only data; an address generator, a start register, and a duration register (144, 150B, 150C, Fig. 2) are used to generate the addresses which correspond to the data and to the target register.

28. Kao discloses a similar system and method of loading configuration registers, where initialization data is stored in a non-volatile memory and subsequently loaded into the registers during system startup. In the system of Kao, an address generator is not used. Instead, the register address is stored in the memory along with the data to be stored. See Fig. 5.

29. Bonaccio and Kao are analogous art because they are from the same area of endeavor, namely systems for loading configuration registers.

30. At the time of the invention it would have been obvious to a person of ordinary skill in the art to modify the system of Bonaccio by replacing the address generator and address registers 150b,c with the address+data system of Kao.

31. The motivation for doing so is taught by Kao on Col. 3, lines 9-15, namely that this increases system efficiency and speed. Because the address is already stored in the memory, the address generator does not need to generate an address; it can simply be loaded with the data.

32. Therefore, it would have been obvious to combine Kao with Bonaccio for the benefit of increased circuit simplicity and speed, to obtain the invention as specified in claim 11, 15.

33. As for claim 12-13, the system of Kao and Bonaccio teaches:

- wherein the test information includes a word of register address information and corresponding register data words for each one of the plurality of registers (see Fig. 5, Kao; the test information includes a register address and corresponding data; see also Bonaccio, last half of Par. 23).

34. As for claim 16, the system of Kao and Bonaccio teaches:

- resetting and loading occur during initialization of a communication controller device (see Bonaccio, ; Kao, Col. 3, lines 27-35: section b; the loading happens on startup).

35. Claims 20-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kao in view of Bonaccio and Cohen, US 5,737,524.

36. Kao teaches

- a plurality of configuration registers of a device (210, Fig. 1),
- a non-volatile memory storing information to load a plurality of configuration registers of a device (160, Fig. 1), wherein
- the information includes a plurality of address information and a plurality of data corresponding to the plurality of address information (see address information 0, 5, 5m, 5n and data information 1-4, 6, 5m+1-5m+4, Fig. 5),
- each of the plurality of address information identifying at least one of the plurality of configuration registers to which a corresponding data should be written (see Fig. 5; the address information is an index referring to the appropriate register; see 365, Fig. 3).
- a block of control logic coupled to the memory, the block of control logic to write the plurality of data to the plurality of configuration registers according to the plurality of address information (see 205, Fig. 2; for multiple logic blocks which control the loading).
- The non-volatile memory is an Electrically Erasable Programmable Read-only Memory (See Col. 3, line 43) and
- the non-volatile memory has a memory size less than or equal to a memory size sufficient to fill all the configuration registers (The memory has a size equal to a

memory size sufficient to fill some or all the configuration registers; see Col. 3, lines 10-15; Claim 2)

37. Kao does not expressly teach that the device is an Ethernet controller device, instead teaching a PCI/ISA bus bridge.

38. Cohen teaches a similar system for loading configuration registers of a PCI/peripheral bus interface (24, Fig. 2) from a non-volatile memory (12D, Fig. 2). Cohen teaches that the PCI bus bridge may be used to interface different devices to the bus, such as an Ethernet device or a SCSI interface (Col. 2, lines 6-10).

39. At the time of the present invention it would have been obvious to one of ordinary skill in the art to modify the system of Kao by using it in an Ethernet controller device.

40. The motivation for doing so is taught by Cohen, in Col. 2, lines 6-28, namely that different devices that use a PCI bus use different configuration register settings. It may be possible to reuse the bus interface chip if the configuration settings are reprogrammable; therefore, the system to load the registers from a reprogrammable memory is used. A further motivation is found in Bonaccio, which also teaches a similar system for loading configuration registers from an EEPROM. Bonaccio teaches in Par. 4 that using programmable registers is widely used in many ICs to allow the user to configure the function of the chip. Further, in Pars. 20-21, he teaches that the methods of loading configuration registers (which are similar to those of the present invention) may be applied not only to ICs such as hard disk channel controllers, but to any IC configured by registers.

41. Therefore, one of ordinary skill would be motivated to use the system of Kao in an Ethernet device as does Cohen, thereby obtaining the invention of claims 20-22.

Allowable Subject Matter

42. Claims 14, 17-19 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

43. The primary reasons for allowance of claims 14 in the instant application is the combination with the inclusion in these claims that the loading occurs during a memory design validation stage. The prior art of record neither anticipates nor renders obvious the above recited combination.

44. The primary reasons for allowance of claims 17 in the instant application is the combination with the inclusion in these claims of the multi-stage test data loading process. The prior art of record neither anticipates nor renders obvious the above recited combination.

45. If the applicant should choose to rewrite the independent claims to include the limitations recited in either one of claims 14, 17-19, the applicant is encouraged to amend the title of the invention such that it is descriptive of the invention as claimed as required by sec. 606.01 of the MPEP. Furthermore, the Summary of the Invention and the Abstract should be amended to bring them into harmony with the allowed claims as required by paragraph 2 of sec. 1302.01 of the MPEP.

46. As allowable subject matter has been indicated, applicant's response must either comply with all formal requirements or specifically traverse each requirement not complied with. See 37 C.F.R. § 1.111(b) and § 707.07(a) of the M.P.E.P


Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Garner, US 5,014,193 teaches a system for loading one of multiple configuration sets for a computer. MacDonald, US 5,768,584, teaches a method for loading configuration data for a memory from a ROM. Davidson, US 5,428,748, teaches a system for loading I/O addresses and configuration data for a peripheral from an EEPROM.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Jesse Diller whose telephone number is (571) 272-4173. The examiner can normally be reached on 8:30AM-5:00PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Donald Sparks can be reached on (571) 272-4201. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

A handwritten signature in black ink, appearing to be a stylized 'JD' or similar initials, located at the bottom left of the page.A handwritten signature in black ink, appearing to be 'Donald Sparks', located at the bottom right of the page.

DONALD SPARKS
SUPERVISORY PATENT EXAMINER